



Specifications Ledvance LED  
Downlight Performance DN155 14W  
1600lm 65D - 840 Cool White | 180mm  
- IP54 - Dali Dimmable

[View Product](#)

General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 238967                             |
| EAN                      | 4058075459311                      |
| Manufacturer Code        | 4058075459311                      |
| Brand                    | Ledvance                           |
| Manufacturer Name        | DL UGR19 DN155 PFM 14W/840 DALI WT |
| Any Lamp all-in warranty | 5 Years                            |
| Average Lifetime (h)     | 70000                              |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 14W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Yes, Dimmable     |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                |
|--------------------------|--------------------------------|
| Driver Included          | Yes                            |
| Beam Angle (degree)      | 65                             |
| Luminous Flux (Lumen)    | 1600lm                         |
| Luminous Efficacy (lm/W) | 115                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 100                            |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

### Fixture Information

---

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 155                    |
| IP-rating              | IP54                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +45             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Colour of material     | White                  |
| Fixture Connection     | Screw terminal, 5-pole |
| Series                 | DN155                  |

### Dimensions

---

|               |     |
|---------------|-----|
| Height (mm)   | 65  |
| Diameter (mm) | 180 |

### Sensor Information

---

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

