



Specifications Multipack 6x Noxion  
LED Downlight Apollo V2.0 6-12W  
720-1500lm 60D - 830/840 CCT |  
145mm - Cutout 120mm



[View Product](#)

## General Information

|                          |                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------|
| SKU                      | 259015                                                                                           |
| EAN                      | 8719157077750                                                                                    |
| Manufacturer Code        | 8719157077750                                                                                    |
| Brand                    | Noxion                                                                                           |
| Manufacturer Name        | Multipack 6x Noxion LED Downlight Apollo V2.0 6/9/12W MAX 1500lm 2CCT Cutout Ø120mm Frame Ø145mm |
| Any Lamp all-in warranty | 6 Years                                                                                          |
| Average Lifetime (h)     | 100000                                                                                           |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 24                               |
| Wattage                     | 12W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 60                             |
| Luminous Flux (Lumen)    | 1500lm                         |
| Luminous Efficacy (lm/W) | 130                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Finish of Reflector      | White                          |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 120                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | Apollo                        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 92  |
| Diameter (mm) | 145 |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process